AQUASHIELD-1

CREW AND PATROL VESSEL

GENERAL DATA

Owner: Aquashield Oil & Marine

Services

Hull: Aluminium Deck House: Aluminium

Wheelhouse: Composite Sandwish with

Ballistic protection.

Description: Crew & Patrol Vessel

Classification: Bureau Veritas

DIMENSIONS

Length: 35m
Beam: 7.5m
Depth at sides: 3.6m
Draught (Max): 1.4m

Displacement: 92 Tons (Lightship)

175 Tons (full Load)

CAPACITIES

Fuel Oil: 56m³
Fresh Water: 10m³
Fresh Water: 4m³
Crew: 6
Security Personnel: 12

ELECTRICAL

Power Supply: 400VAC Generator: 2x Caterpillar C4.4 107KV.

PROPULSION

Engines: 3 x Caterpillar C32 ACERT

Power: 3 x 1193K
Propulsion: 3 x Propellers
Remote Engine Monitoring
CJC Fuel filtration system

PERFORMANCE

Speed @ cruise: 20 knots Speed @ Full: 28 knots Range @10knots: 4100nm Range @ 20knots: 1150nm



NAVIGATION & COMMUNICATION

Packaged according to the rules for GMDSS-A3. The following equipment is fitted as

standard:

VHF with DCS
MF/HF with DCS
Radar 6kw x 2
GPS/Chart Plotter

AIS

Magnetic & Fluxgate Compass

Handheld VHF's (x2)

EPIRB SART Navtec

LIFE SAVING & SAFETY

Life Rafts: 4 x 20pax SOLAS liferafts, Life Jackets 48 SOLAS life-jackets

Fixed Fire Fighting: FM 200 in Engine Room

Portable Fire Extinguisher

DECK LAYOUT

Anchor: 1 x HHP Anchor 140kg

Deck Area(Storage): 65m²

ACCOMMODATION

4 Man Cabins insuite: 2
2 Man Cabins insuite: 4
1 Man Cabins Insuite: 2
Passenger seating: 16

Walk in freezer and chiller Rooms

CCTV

FLIR Camera



Aquashield Oil & Marine Services Ltd

10 Nyeweli Nsirim Layout, off Tombia Extension, GRA Phase 2, Port Hacourt, Rivers State, Nigeria





